

1		2		3		4		5		6		7		8																																																											
ROHS														For reference only																																																											
A	<table><tr><td>Pin数</td><td>尺寸A</td></tr><tr><td>2×6</td><td>10.00</td></tr><tr><td>2×8</td><td>14.00</td></tr><tr><td>2×10</td><td>18.00</td></tr><tr><td>2×12</td><td>22.00</td></tr><tr><td>2×14</td><td>26.00</td></tr><tr><td>2×16</td><td>30.00</td></tr><tr><td>2×18</td><td>34.00</td></tr><tr><td>2×20</td><td>38.00</td></tr><tr><td>2×22</td><td>42.00</td></tr><tr><td>2×24</td><td>46.00</td></tr><tr><td>2×26</td><td>50.00</td></tr><tr><td>2×28</td><td>54.00</td></tr><tr><td>2×30</td><td>58.00</td></tr><tr><td>2×32</td><td>62.00</td></tr><tr><td>2×34</td><td>66.00</td></tr><tr><td>2×36</td><td>70.00</td></tr><tr><td>2×38</td><td>74.00</td></tr><tr><td>2×40</td><td>78.00</td></tr><tr><td>2×42</td><td>82.00</td></tr><tr><td>2×44</td><td>86.00</td></tr><tr><td>2×46</td><td>90.00</td></tr><tr><td>2×48</td><td>94.00</td></tr><tr><td>2×50</td><td>98.00</td></tr><tr><td>2×52</td><td>102.00</td></tr><tr><td>2×54</td><td>106.00</td></tr><tr><td>2×56</td><td>110.00</td></tr><tr><td>2×58</td><td>114.00</td></tr><tr><td>2×60</td><td>118.00</td></tr></table>		Pin数	尺寸A	2×6	10.00	2×8	14.00	2×10	18.00	2×12	22.00	2×14	26.00	2×16	30.00	2×18	34.00	2×20	38.00	2×22	42.00	2×24	46.00	2×26	50.00	2×28	54.00	2×30	58.00	2×32	62.00	2×34	66.00	2×36	70.00	2×38	74.00	2×40	78.00	2×42	82.00	2×44	86.00	2×46	90.00	2×48	94.00	2×50	98.00	2×52	102.00	2×54	106.00	2×56	110.00	2×58	114.00	2×60	118.00													A
Pin数	尺寸A																																																																								
2×6	10.00																																																																								
2×8	14.00																																																																								
2×10	18.00																																																																								
2×12	22.00																																																																								
2×14	26.00																																																																								
2×16	30.00																																																																								
2×18	34.00																																																																								
2×20	38.00																																																																								
2×22	42.00																																																																								
2×24	46.00																																																																								
2×26	50.00																																																																								
2×28	54.00																																																																								
2×30	58.00																																																																								
2×32	62.00																																																																								
2×34	66.00																																																																								
2×36	70.00																																																																								
2×38	74.00																																																																								
2×40	78.00																																																																								
2×42	82.00																																																																								
2×44	86.00																																																																								
2×46	90.00																																																																								
2×48	94.00																																																																								
2×50	98.00																																																																								
2×52	102.00																																																																								
2×54	106.00																																																																								
2×56	110.00																																																																								
2×58	114.00																																																																								
2×60	118.00																																																																								
B															B																																																										
C															C																																																										
D															D																																																										
E	Specification: Current Rating : 1.5AMP Temperature Range : -40℃to+105℃ Contact Resistance : 20mΩ Max Insulation Resistance : 1000MΩ Min Withstanding Voltage : AC 500V Material: Insulator : Polyester (UL94V-0) Standard:PA6T/LCP Contact: Brass Plating : Au or Sn Over 50u" Ni														E																																																										
F															F																																																										
G															G																																																										
H	<table><tr><td></td><td></td><td></td><td rowspan="4"></td><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td rowspan="4">NAME</td><td rowspan="4">DATE</td><td rowspan="4"> 深圳市联索连接器有限公司 SHENZHEN UNICABLE CONNECTOR CO., LTD. 公司网址WWW.SZLSTC.CN 公司邮箱SZLSTC@126.COM 公司电话0755-23765650 公司传真0755-23765753</td><td colspan="2">PART. NO: LSEH-0013-01</td></tr><tr><td></td><td></td><td></td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td><td>DWG. NO:</td></tr><tr><td></td><td></td><td></td><td>0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td><td>ENDE3013-01</td></tr><tr><td></td><td></td><td></td><td>0.00±0.15</td><td>X° ±3°</td><td>DRAWN</td><td></td><td>REV: A0 SHEET: 1/1</td></tr><tr><td>REV.</td><td colspan="2">REVISION RECORD</td><td>DATE</td><td>UNIT: MM</td><td>SIZE: A4</td><td>0.000±0.08</td><td>X° X'±2°</td><td colspan="2">TITLE: Pitch2.00mm Ejector Header, Dual Row, Plastic Height 7.24mm, SMT Type</td><td colspan="2"></td></tr></table>																		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 深圳市联索连接器有限公司 SHENZHEN UNICABLE CONNECTOR CO., LTD. 公司网址WWW.SZLSTC.CN 公司邮箱SZLSTC@126.COM 公司电话0755-23765650 公司传真0755-23765753	PART. NO: LSEH-0013-01					LINEAR	ANGLES	APPROVED		DWG. NO:				0.0±0.25	X° REF±6°	DESIGNER		ENDE3013-01				0.00±0.15	X° ±3°	DRAWN		REV: A0 SHEET: 1/1	REV.	REVISION RECORD		DATE	UNIT: MM	SIZE: A4	0.000±0.08	X° X'±2°	TITLE: Pitch2.00mm Ejector Header, Dual Row, Plastic Height 7.24mm, SMT Type				H										
				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 深圳市联索连接器有限公司 SHENZHEN UNICABLE CONNECTOR CO., LTD. 公司网址WWW.SZLSTC.CN 公司邮箱SZLSTC@126.COM 公司电话0755-23765650 公司传真0755-23765753	PART. NO: LSEH-0013-01																																																															
				LINEAR	ANGLES	APPROVED					DWG. NO:																																																														
				0.0±0.25	X° REF±6°	DESIGNER					ENDE3013-01																																																														
				0.00±0.15	X° ±3°	DRAWN					REV: A0 SHEET: 1/1																																																														
REV.	REVISION RECORD		DATE	UNIT: MM	SIZE: A4	0.000±0.08	X° X'±2°	TITLE: Pitch2.00mm Ejector Header, Dual Row, Plastic Height 7.24mm, SMT Type																																																																	
1		2		3		4		5		6		7		8																																																											